

MODEL


GM900 系列

超高速直驱式包缝机

Super High speed overlock sewing machine
with direct drive

GM900-3Z/-4Z/-5Z

GM900-3DZ/-4DZ/-5DZ



GM900-4DZ直驱式四线超高速自动包缝机

本系列包缝机均设计采用了内置式伺服电机直接驱动，控制系统性能卓越，稳定可靠。产品在结构上吸收了国际先进水平的优点，性能上突出了市场需求的适应面广、实用性强的特点。本系列中除基本款以外，多款机型具有自动剪线、自动抬压脚、气动废料吸收收集尘装置（选购），省电高效，是集机械与电控技术于一身的机电一体化产品。


本系列产品主要部位装有滚珠或滚针轴承，高速运转时轻滑，采用全封闭润滑系统和硅油冷却机针装置，差动牙微量调节和按钮式针距调节装置。缝线、切刀以及弯针的调整极为方便。适用于各种薄料、中厚料织物的包边、包缝，是针织、服装、衬衫厂高效的缝纫设备。

- GM900-3Z 直驱式三线超高速包缝机
- GM900-3DZ 直驱式自动剪线三线超高速包缝机
- GM900-4Z 直驱式四线超高速包缝机
- GM900-4DZ 直驱式自动剪线四线超高速包缝机
- GM900-5Z 直驱式五线超高速包缝机
- GM900-5DZ 直驱式自动剪线五线超高速包缝机

This series overlock is built-in mini servo motor for direct drive, fine and stable control system and electromechanical. The machine is designed with fashionable appearance and world advanced mechanism. It features wide and practical application. Many models have features of automatic thread trimmer, automatic presser foot lifter, pneumatic rubbish collection device (optional). The series is high efficiency of energy saving.

This series of overlock sewing machines is equipped with ball bearing or needle bearing which makes it running light and smooth, fully closed lubrication system, silicon oil needle cooling device, fine adjustment of differential feed dog and knob-type stitch regulator. It is also convenient to adjust the thread, the knife and the loopers and can perform overlock and overedge on all kinds of fabric from light to medium heavy weight as an efficient sewing equipment in knitting and garment factories.

- GM900-3Z Three threads super high speed overlock with direct drive
- GM900-3DZ Three threads super high speed overlock with automatic thread trimmer and direct drive
- GM900-4Z Four threads super high speed overlock with direct drive
- GM900-4DZ Four threads super high speed overlock with automatic thread trimmer and direct drive
- GM900-5Z Five threads super high speed overlock with direct drive
- GM900-5DZ Five threads super high speed overlock with automatic thread trimmer and direct drive



主要技术参数 Main technical specifications

型号 Model	最高缝速 Max. sewing speed	机针 Needle size	机针数 Number of needle	缝线数 Number of thread	线迹长度 Stitch length	线迹宽度 Stitch width	压脚提升 Presser foot lift	差动比 Differential ratio	自动剪线 Auto trimmer	自动抬压脚 Auto presser foot lifter
GM900-3Z	7000 r.p.m.	DC × 27 11#	1	3	3.8 mm	4 mm	5.5 mm	0.7 - 2	○	○
GM900-3DZ	7000 r.p.m.	DC × 27 11#	1	3	3.8 mm	4 mm	5.5 mm	0.7 - 2	★	★
GM900-4Z	7000 r.p.m.	DC × 27 11#	2	4	3.8 mm	4 mm	5.5 mm	0.7 - 2	○	○
GM900-4DZ	7000 r.p.m.	DC × 27 11#	2	4	3.8 mm	4 mm	5.5 mm	0.7 - 2	★	★
GM900-5Z	7000 r.p.m.	DC × 27 14#	2	5	5 mm	4 mm	5.5 mm	0.7 - 2	○	○
GM900-5DZ	7000 r.p.m.	DC × 27 14#	2	5	5 mm	4 mm	5.5 mm	0.7 - 2	★	★