

MODEL

GC20618-DZA 系列

直驱式自动剪线综合送料厚料平缝机

Direct drive heavy duty compound feed lockstitch sewing machine with auto thread trimmer

GC20618-1DZA

GC20618-2DZA



GC20618-2DZA直驱式自动剪线双针综合送料厚料平缝机

本系列机型设计搭载小型大功率伺服电机直接驱动，噪音低、振动小、节能显著，安装便捷。外形设计新颖流畅，具有海菱品牌特色及时代气息。嵌入式操作面板，电子手轮及 LED 缝纫照明灯的配置，使缝制过程显得更为轻松方便，令操作者舒适愉悦。设计采用了双夹线机构，使缝制物品线迹更为平整美观。电磁式夹线装置实现了起缝无多余线头，不会产生起针脱线和鸟巢现象。短线头剪线装置(仅限于 GC20618-1DZA 机型)使切线后的余线极短。压脚提升和倒缝采用气动控制，极大地减轻操作者的劳动强度。

本机分为单针和双针两款，双针机型的针间距有多种选择，采用自动剪线和自动润滑装置，保证了机器的运转轻滑和经久耐用。是海菱 GC20618 系列产品的升级版。特别适用于汽车坐垫、安全带、汽车内饰、沙发、箱包、帐篷等厚料物品的缝制。

GC20618-1DZA 直驱式自动剪线单针

GC20618-2DZA 双针综合送料厚料平缝机(加长型)

This series is designed with powerful built-in mini servo motor for direct drive, featuring low noise, low vibration, energy saving and convenient installation. The new appearance is smooth and characteristic of Highlead and modern style. The embedded operation panel, electronic dial and LED make sewing processing easy and relaxed. Its dual electromagnetic thread tension mechanism helps to produce smooth and beautiful stitches and there will be no excess thread and no thread skipping and no bird's nest at start. The short thread end trimmer (only available with GC20618-1DZA) makes the thread end very short after trimming. Equipped with pneumatic presser foot lifter and pneumatic backtacking, it greatly reduces the work intensity of the operators.

This series is classified into single needle and two needle. For two needle class, it has a good choice of needle gauges. The auto lubrication assures the smooth running and durability of the machine. It is an upgraded version of Highlead brand GC20618 series, especially available in stitching car seat, safety belt, automotive interior, sofa, luggage, tent, etc.

GC20618-1DZA/2DZA Single needle/Two needle direct drive heavy duty compound feed lockstitch sewing machine with auto thread trimmer (Arm lengthened)



型号 Model	最高缝速 Max sewing speed	线迹长度 Stitch length	压脚提升 Presser foot lift	机针 Needle size	安全离合装置 Safety clutch device	自动剪线装置 Auto trimmer	自动抬压脚装置 Auto foot lifting device
GC20618-1DZA	2500 r.p.m.	0 - 9 mm	气动 Presser foot lift 17 mm (pneumatic)	DP × 17 18°-23°	★	★	★
GC20618-2DZA	2500 r.p.m.	0 - 9 mm	气动 Presser foot lift 17 mm (pneumatic)	DP × 17 18°-23°	★	★	★
型号 Model	自动润滑装置 Auto lubrication	电子手轮装置 Electronic dial	面线张力切换装置 Upper thread tension change-over device	自动倒缝装置 Auto backtacking	短线头剪线头装置 Short thread end trimmer	操作空间 Working space	电动机 Motor
GC20618-1DZA	★	★	★	★	★	300 × 118 mm	220 伏 750 瓦伺服电机 220V 750W servo motor
GC20618-2DZA	★	★	★	★	○	300 × 118 mm	220 伏 750 瓦伺服电机 220V 750W servo motor
针间距 Needle gauge		GC20618-2DZ GC20618-2DZA 标准 Standard 6.4 mm 特殊 Special 3.2 4.8 8 9.5 12.7 mm					

特殊规格针间距请在订货时指定
Please specify for special needle gauge when ordering